

# CD265 SERIES



## ALUMINUM ELECTROLYTIC CAPACITORS



- Load life of 1000 hours at 125°C

### ■ SPECIFICATIONS

Item	Characteristics																										
Operating Temperature Range(°C)	-40~+125																										
Rated Voltage Range (V)	10~100																										
Nominal capacitance range (μF)	0.47~1000																										
Capacitance Tolerance(20°C,120Hz)	±20%																										
Leakage current (μA)	$I \leq 0.02CV$ or $2 \mu A$ whichever is greater. (at 20°C, after 2 minutes) C: Nominal Capacitance (μF) V: Rated Voltage (V)																										
Dissipation Factor(20°C,120Hz)	<table border="1"> <thead> <tr> <th>Rated voltage (V)</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> <th>100</th> </tr> </thead> <tbody> <tr> <td>tanδ</td> <td>0.20</td> <td>0.17</td> <td>0.17</td> <td>0.12</td> <td>0.10</td> <td>0.10</td> <td>0.10</td> </tr> </tbody> </table>	Rated voltage (V)	10	16	25	35	50	63	100	tanδ	0.20	0.17	0.17	0.12	0.10	0.10	0.10										
Rated voltage (V)	10	16	25	35	50	63	100																				
tanδ	0.20	0.17	0.17	0.12	0.10	0.10	0.10																				
Temperature Stability(120Hz)	<table border="1"> <thead> <tr> <th colspan="2">Rated Voltage (V)</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> <th>100</th> </tr> </thead> <tbody> <tr> <td rowspan="2">Impedance Ratio</td> <td>Z-25°C/Z+20°C</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> </tr> <tr> <td>Z-40°C/Z+20°C</td> <td>8</td> <td>6</td> <td>4</td> <td>4</td> <td>4</td> <td>4</td> <td>3</td> </tr> </tbody> </table>	Rated Voltage (V)		10	16	25	35	50	63	100	Impedance Ratio	Z-25°C/Z+20°C	2	2	2	2	2	2	2	Z-40°C/Z+20°C	8	6	4	4	4	4	3
Rated Voltage (V)		10	16	25	35	50	63	100																			
Impedance Ratio	Z-25°C/Z+20°C	2	2	2	2	2	2	2																			
	Z-40°C/Z+20°C	8	6	4	4	4	4	3																			
Load Life(+125°C)	<table border="1"> <thead> <tr> <th>Time</th> <th>1000 hours</th> </tr> </thead> <tbody> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> </tr> <tr> <td>Capacitance Change</td> <td>Within ±15% of the initial value.</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 150% of the specified value.</td> </tr> </tbody> </table>	Time	1000 hours	Leakage Current	Not more than the specified value.	Capacitance Change	Within ±15% of the initial value.	Dissipation Factor	Not more than 150% of the specified value.																		
Time	1000 hours																										
Leakage Current	Not more than the specified value.																										
Capacitance Change	Within ±15% of the initial value.																										
Dissipation Factor	Not more than 150% of the specified value.																										
Shelf Life(+125°C)	<table border="1"> <thead> <tr> <th>Time</th> <th>500 hours</th> </tr> </thead> <tbody> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> </tr> <tr> <td>Capacitance Change</td> <td>Within ±15% of the initial value.</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 150% of the specified value.</td> </tr> </tbody> </table>	Time	500 hours	Leakage Current	Not more than the specified value.	Capacitance Change	Within ±15% of the initial value.	Dissipation Factor	Not more than 150% of the specified value.																		
Time	500 hours																										
Leakage Current	Not more than the specified value.																										
Capacitance Change	Within ±15% of the initial value.																										
Dissipation Factor	Not more than 150% of the specified value.																										

After test: Rated voltage to be applied for 30 minutes, 24 to 48 hours before measurement.

### ■ DIMENSIONS

MM

### ■ MULTIPLIER FOR RIPPLE CURRENT

<p>Safety Vent</p>		<h4>Frequency coefficient</h4> <table border="1"> <thead> <tr> <th>Freq(Hz)</th> <th>50,60</th> <th>120</th> <th>500</th> <th>1K</th> <th>≥10K</th> </tr> </thead> <tbody> <tr> <td>Cap(μF)</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.47~47</td> <td>0.8</td> <td>1.0</td> <td>1.2</td> <td>1.3</td> <td>1.5</td> </tr> <tr> <td>100~1000</td> <td>0.8</td> <td>1.0</td> <td>1.1</td> <td>1.15</td> <td>1.2</td> </tr> </tbody> </table>					Freq(Hz)	50,60	120	500	1K	≥10K	Cap(μF)						0.47~47	0.8	1.0	1.2	1.3	1.5	100~1000	0.8	1.0	1.1	1.15	1.2
Freq(Hz)	50,60	120	500	1K	≥10K																									
Cap(μF)																														
0.47~47	0.8	1.0	1.2	1.3	1.5																									
100~1000	0.8	1.0	1.1	1.15	1.2																									
<h4>Lead spacing and diameter</h4> <table border="1"> <thead> <tr> <th rowspan="2">ΦD</th> <th>±0.5</th> <th colspan="3">±1.0</th> </tr> <tr> <th>8</th> <th>10</th> <th>12.5</th> <th>16</th> </tr> </thead> <tbody> <tr> <td>F±0.5</td> <td>3.5</td> <td>5.0</td> <td>5.0</td> <td>7.5</td> </tr> <tr> <td>Φd±0.1</td> <td>0.6</td> <td>0.6</td> <td>0.6</td> <td>0.8</td> </tr> <tr> <td>a</td> <td colspan="4">0~+2.0</td> </tr> </tbody> </table>							ΦD	±0.5	±1.0			8	10	12.5	16	F±0.5	3.5	5.0	5.0	7.5	Φd±0.1	0.6	0.6	0.6	0.8	a	0~+2.0			
ΦD	±0.5	±1.0																												
	8	10	12.5	16																										
F±0.5	3.5	5.0	5.0	7.5																										
Φd±0.1	0.6	0.6	0.6	0.8																										
a	0~+2.0																													

## ■ STANDARD RATINGS

WV(V)	10		16		25		35		50		63		100	
Cap(μF)	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple
	ΦDxL(mm)	(mA)	ΦDxL(mm)	(mA)	ΦDxL(mm)	(mA)	ΦDxL(mm)	(mA)	ΦDxL(mm)	(mA)	ΦDxL(mm)	(mA)	ΦDxL(mm)	(mA)
0.47	-	-	-	-	-	-	-	-	8x11.5	3.6	-	-	8x11.5	4.8
1	-	-	-	-	-	-	-	-	8x11.5	9	-	-	8x11.5	12
2.2	-	-	-	-	-	-	-	-	8x11.5	18	-	-	8x11.5	24
3.3	-	-	-	-	-	-	-	-	8x11.5	27	8x11.5	30	10x12.5	33
4.7	-	-	-	-	-	-	-	-	8x11.5	33	8x11.5	36	10x12.5	39
10	-	-	-	-	-	-	-	-	8x11.5	51	8x11.5	54	10x20	57
22	-	-	-	-	-	-	8x11.5	72	10x12.5	90	10x12.5	96	12.5x25	102
33	-	-	-	-	8x11.5	72	10x12.5	102	10x12.5	114	10x16	126	16x25	150
47	-	-	8x11.5	81	8x11.5	87	10x12.5	120	10x16	150	10x20	171	16x25	192
100	8x11.5	105	10x12.5	141	10x16	165	10x20	222	12.5x20	282	12.5x25	306	-	-
220	10x16	207	10x20	261	10x20	279	12.5x25	405	16x25	510	16x25	525	-	-
330	10x16	252	12.5x20	360	12.5x25	420	16x25	573	16x25	642	-	-	-	-
470	10x20	342	12.5x25	462	16x25	573	16x31.5	762	-	-	-	-	-	-
1000	16x25	708	16x25	774	-	-	-	-	-	-	-	-	-	-

## ■ Ripple Current: 125°C, 100 or 120Hz

The specific capacitance and case size are available on request.